

Safety Data Sheet

Section 1: Identification

Product identifier

- Product Name** • **Natural Gas**
- Synonyms** • Natural gas-dry; Pipeline gas
- SDS Number/Grade** • NG 2008-01

Relevant identified uses of the substance or mixture and uses advised against

- Recommended use** • Residential, commercial and industrial heating, industrial feedstock, power generation and vehicle transportation

Details of the supplier of the safety data sheet

- Manufacturer** • NW Natural
220 NW 2nd Ave.
Portland, OR 97209
United States
www.nwnatural.com
- Telephone (General)** • 800-422-4012

Emergency telephone number

- Manufacturer** • 800-882-3377

Section 2: Hazard Identification

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

- OSHA HCS 2012** • Flammable Gases 1 - H220
Compressed Gas - H280
Simple Asphyxiant

Label elements

OSHA HCS 2012

DANGER



- Hazard statements** • Extremely flammable gas - H220
Contains gas under pressure; may explode if heated - H280
May displace oxygen and cause rapid suffocation.

Precautionary statements

- Prevention** • Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking. - P210
- Response** • Leaking gas fire: Do not extinguish, unless leak can be stopped safely. - P377
Eliminate all ignition sources if safe to do so. - P381

Storage/Disposal • Protect from sunlight. Store in a well-ventilated place. - P410+P403

Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Section 3 - Composition/Information on Ingredients

Substances

- Material does not meet the criteria of a substance.

Mixtures

Composition				
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive
Methane	CAS:74-82-8	93.5%	NDA	OSHA HCS 2012: Flam. Gas 1; Press. Gas - Comp.; Simp. Asphyx.
Ethane	CAS:74-84-0	3.8%	NDA	OSHA HCS 2012: Flam. Gas 1; Press. Gas - Comp., Simp. Asphyx.
Nitrogen	CAS:7727-37-9	1.2%	NDA	OSHA HCS 2012: Press. Gas - Comp.; Simp. Asphyx.
Propane	CAS:74-98-6	1%	NDA	OSHA HCS 2012: Flam. Gas 1; Press. Gas - Comp., Simp. Asphyx.
Carbon dioxide	CAS:124-38-9	0.3%	Inhalation-Rat LC50 • 470000 ppm 30 Minute(s)	OSHA HCS 2012: Press. Gas - Comp.; Simp. Asphyx.
Isobutane	CAS:75-28-5	0.1%	Inhalation-Rat LC50 • 658000 mg/m ³ 4 Hour(s)	OSHA HCS 2012: Flam. Gas 1; Press Gas - Comp.; Simp. Asphyx.
Butane	CAS:106-97-8	0.1%	Inhalation-Rat LC50 • 658 g/m ³ 4 Hour(s)	OSHA HCS 2012: Flam. Gas 1; Press Gas - Comp.; Simp. Asphyx.
Pentane	CAS:109-66-0	< 0.1%	Inhalation-Rat LC50 • 364 g/m ³ 4 Hour(s)	OSHA HCS 2012: Exposure limit(s)
Hexane	CAS:110-54-3	< 0.1%	Inhalation-Rat LC50 • 627000 mg/m ³ 3 Minute(s)	OSHA HCS 2012: Exposure limit(s)
2-Methylbutane (In Liquid form)	CAS:78-78-4	< 0.1%	Inhalation-Rat LC50 • 280000 mg/m ³ 4 Hour(s)	OSHA HCS 2012: Exposure limit(s)
2-Propanethiol, 2-methyl-	CAS:75-66-1	< 30ppm	Ingestion/Oral-Rat LD50 • 4729 mg/kg Inhalation-Rat LC50 • 22200 ppm 4 Hour(s)	OSHA HCS 2012: Exposure limit(s)
Methyl ethyl sulfide	CAS:624-89-5	< 8ppm	NDA	OSHA HCS 2012: Exposure limit(s)
Hydrogen sulfide	CAS:7783-06-4	< 5ppm	Inhalation-Rat LC50 • 700 mg/m ³ 4 Hour(s)	OSHA HCS 2012: Exposure limit(s)

All percentages provided are approximate.

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

- Although exposure is unlikely, in case of contact immediately flush skin with running water. If skin irritation develops get medical advice/attention.

Eye

- First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If irritation develops and persists, get medical attention.

Ingestion

- Ingestion is not considered a potential route of exposure.

Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. A potential health hazard associated with this gas is anoxia.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • Dry Chemical, (Potassium Bicarbonate based *Purple K* most effective), Carbon dioxide, Water.

Unsuitable Extinguishing Media

- No data available

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

- EXTREMELY FLAMMABLE
Will form explosive mixtures with air.
Vapors may travel to source of ignition and flash back.
Cylinders exposed to fire may vent and release flammable gas through pressure relief devices.
Containers may explode when heated.
Ruptured cylinders may rocket.

Hazardous Combustion Products

- No data available

Advice for firefighters

- Gas fires should not be extinguished unless flow of gas can be stopped. Only authorized personnel should turn off valves or attempt repairs. Fire crews should wear self-contained breathing apparatus (SCBA). Natural gas is lighter than air and will vent upward but special consideration should be given to areas that may trap or contain explosive concentrations including areas of potential migration underground or through structures. Water mist may be used to cool surrounding structures including compressed gas cylinders or tanks.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ventilate the area before entry.

Emergency Procedures

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions. Stop leak if you can do it without risk. Keep unauthorized personnel away. Keep out of low areas. Stay upwind. **LARGE SPILL:**

Consider initial downwind evacuation for at least 800 meters (1/2 mile)

Environmental precautions

- Prevent spreading of vapors through sewers, ventilation systems and confined areas.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

- All equipment used when handling the product must be grounded. Stop leak if you can do it without risk. If possible, turn leaking containers so that gas escapes rather than liquid. Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container. Do not direct water at spill or source of leak. Isolate area until gas has dispersed.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

- Keep away from heat and ignition sources – No Smoking. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. Use only non-sparking tools. Use only with adequate ventilation. Ventilate closed spaces before entering. Be aware of any signs of dizziness or fatigue, especially if work is done in a poorly ventilated area; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms, due to olfactory fatigue or oxygen deficiency. Cylinders should be firmly secured to prevent falling or being knocked-over. Use explosion-proof - electrical, ventilating and/or lighting equipment. Do not attempt to repair, adjust, or in any other way modify cylinders. If there is a malfunction or another type of operational problem, contact nearest distributor immediately. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

Conditions for safe storage, including any incompatibilities

Storage

- Store in a cool/low-temperature, well-ventilated dry place away from heat and ignition sources. Protect cylinders against physical damage. Cylinders should be firmly secured to prevent falling or being knocked-over.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines				
	Result	ACGIH	NIOSH	OSHA
Pentane (109-66-0)	TWAs	600 ppm TWA (listed under Pentane, all isomers)	120 ppm TWA; 350 mg/m ³ TWA	1000 ppm TWA; 2950 mg/m ³ TWA
	Ceilings	Not established	610 ppm Ceiling (15 min); 1800 mg/m ³ Ceiling (15 min)	Not established
Hexane (110-54-3)	TWAs	50 ppm TWA	50 ppm TWA; 180 mg/m ³ TWA	500 ppm TWA; 1800 mg/m ³ TWA
Isobutane (75-28-5)	STELs	1000 ppm STEL	Not established	Not established
	TWAs	Not established	800 ppm TWA; 1900 mg/m ³ TWA	Not established
Butane (106-97-8)	STELs	1000 ppm STEL	Not established	Not established
	TWAs	Not established	800 ppm TWA; 1900 mg/m ³ TWA	Not established
2-Methylbutane (In Liquid form) (3-78-4)	TWAs	600 ppm TWA (listed under Pentane, all isomers)	Not established	Not established
Carbon dioxide	TWAs	5000 ppm TWA	5000 ppm TWA; 9000 mg/m ³ TWA	5000 ppm TWA; 9000 mg/m ³ TWA

(124-38-9)	STELs	30000 ppm STEL	30000 ppm STEL; 54000 mg/m ³ STEL	Not established
Propane (74-98-6)	TWAs	1000 ppm TWA (listed under Aliphatic hydrocarbon gases: Alkane C1-4)	1000 ppm TWA; 1800 mg/m ³ TWA	1000 ppm TWA; 1800 mg/m ³ TWA
Ethane (74-84-0)	TWAs	1000 ppm TWA (listed under Aliphatic hydrocarbon gases: Alkane C1-4)	Not established	Not established
Hydrogen sulfide (7783-06-4)	Ceilings	Not established	10 ppm Ceiling (10 min); 15 mg/m ³ Ceiling (10 min)	20 ppm Ceiling
	STELs	5 ppm STEL	Not established	Not established
	TWAs	1 ppm TWA	Not established	Not established
Methane (74-82-8)	TWAs	1000 ppm TWA (listed under Aliphatic hydrocarbon gases: Alkane C1-4)	Not established	Not established

Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof - electrical, ventilating and/or lighting equipment.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear safety glasses.

Skin/Body

- Wear leather gloves when handling cylinders.

Environmental Exposure Controls

- Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

NIOSH = National Institute of Occupational Safety and Health

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

OSHA = Occupational Safety and Health Administration

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Gas	Appearance/Description	Colorless, tasteless gas that has no odor or if trace amounts of sulfur compounds are added as an odorant the gas has a garlic/rotten-egg/skunk odor.
Color	Colorless	Odor	Odorless or with trace amounts of sulfur compounds added as an odorant resulting in a garlic/rotten-egg/skunk odor.
Odor Threshold	No data available		
General Properties			

Bolling Point	-258.7 F(-161.5 C) at 14.73 psig	Melting Point	No data available
Composition Temperature	No data available	pH	No data available
Specific Gravity/Relative Density	0.55 to 0.64 Water=1 depending on composition	Density	0.044 lb(s)/ft ³
Bulk Density	No data available	Water Solubility	Slightly Soluble 0.1 to 1 %
Viscosity	No data available		
Volatility			
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available		
Flammability			
Flash Point	-306 F(-187.7778 C)	UEL	15 % Limits vary slightly with composition
LEL	4.8 % Limits vary slightly with composition	Autoignition	1004 F(540 C)
Flammability (solid, gas)	Flammable gas.		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

- No dangerous reaction known under conditions of normal use.

Chemical stability

- Stable under normal temperatures and pressures.

Possibility of hazardous reactions

- Hazardous polymerization will not occur.

Conditions to avoid

- Keep away from heat, sparks, and flame.

Incompatible materials

- Strong oxidizers.

Hazardous decomposition products

- Oxides of carbon (CO, CO₂), "soot"

Section 11 - Toxicological Information

Information on toxicological effects

Components		
Methane (93.5%)	74-82-8	Acute Toxicity: Inhalation-Mouse LC50 • 326 g/m ³ 2 Hour(s)
Isobutane (0.1%)	75-28-5	Acute Toxicity: Inhalation-Rat LC50 • 57 pph 15 Minute(s); Behavioral:Tremor; Behavioral:Convulsions or effect on seizure threshold; Lungs, Thorax, or Respiration:Respiratory depression
Butane (0.1%)	106-97-8	Acute Toxicity: Inhalation-Rat LC50 • 658 g/m ³ 4 Hour(s)

2-Methylbutane (In Liquid form) (< %)	78-78-4	Acute Toxicity: Inhalation-Rat LC50 • 280000 mg/m ³ 4 Hour(s)
Pentane (< 0.1%)	109-66-0	Acute Toxicity: Ingestion/Oral-Rat LD50 • >2000 mg/kg
Hexane (< 0.1%)	110-54-3	Acute Toxicity: Ingestion/Oral-Rat LD50 • 25 g/kg; Inhalation-Rat LC50 • 48000 ppm 4 Hour(s); Irritation: Eye-Rabbit • 10 mg • Mild Irritation
Carbon dioxide (0.3%)	124-38-9	Acute Toxicity: Inhalation-Rat LC50 • 470000 ppm 30 Minute(s); Reproductive: Inhalation-Rat TCLo • 6 pph 24 Hour(s)(10D preg); <i>Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Reproductive Effects:Specific Developmental Abnormalities:Cardiovascular (circulatory) system; Reproductive Effects:Specific Developmental Abnormalities:Respiratory system</i>

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • No data available
Aspiration Hazard	OSHA HCS 2012 • No data available
Carcinogenicity	OSHA HCS 2012 • No data available
Germ Cell Mutagenicity	OSHA HCS 2012 • No data available
Skin corrosion/Irritation	OSHA HCS 2012 • No data available
Skin sensitization	OSHA HCS 2012 • No data available
STOT-RE	OSHA HCS 2012 • No data available
STOT-SE	OSHA HCS 2012 • No data available
Toxicity for Reproduction	OSHA HCS 2012 • No data available
Respiratory sensitization	OSHA HCS 2012 • No data available
Serious eye damage/Irritation	OSHA HCS 2012 • No data available

Route(s) of entry/exposure • Inhalation, Skin, Eye, Ingestion

Potential Health Effects

Inhalation

Acute (Immediate)

- If this material is released in a small, poorly ventilated area (i.e. an enclosed or confined space), an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of over-exposure, death may occur. The following effects associated with decreased levels of oxygen: increase in breathing and pulse rate, emotional upset, abnormal fatigue, nausea, vomiting, collapse, loss of consciousness, convulsive movements, respiratory collapse and death.

Chronic (Delayed)

- No data available

Skin

Acute (Immediate)

- Under normal conditions of use, no health effects are expected.

Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.

Eye

Acute (Immediate)

- Under normal conditions of use, no health effects are expected.

Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.

Ingestion

Acute (Immediate)

- Ingestion is not anticipated to be a likely route of exposure to this product.

Chronic (Delayed)

- Ingestion is not anticipated to be a likely route of exposure to this product.

Key to abbreviations

- = Lethal Dose
- = Mild
- TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

- Material data lacking.

Persistence and degradability

- Material data lacking.

Bioaccumulative potential

- Material data lacking.

Mobility in Soil

- Material data lacking.

Results of PBT and vPvB assessment

- PBT and vPvB assessment has not been conducted for this material.

Other adverse effects

- No studies have been found.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	UN1971	Methane, compressed or Natural gas, compressed (with high methane content)	2.1	NDA	NDA

Special precautions for user

- Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards. If transporting these cylinders in vehicles, ensure these cylinders are not exposed to extremely high temperatures (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated during transportation.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

- Not relevant.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture**RA Hazard Classifications** • Acute, Fire, Pressure(Sudden Release of)

Inventory		
Component	CAS	TSCA
2-Methylbutane (In Liquid form)	78-78-4	Yes
2-Propanethiol, 2-methyl-	75-66-1	Yes
Butane	106-97-8	Yes
Carbon dioxide	124-38-9	Yes
Ethane	74-84-0	Yes
Hexane	110-54-3	Yes
Hydrogen sulfide	7783-06-4	Yes
Isobutane	75-28-5	Yes
Methane	74-82-8	Yes
Methyl ethyl sulfide	624-89-5	Yes
Nitrogen	7727-37-9	Yes
Pentane	109-66-0	Yes
Propane	74-98-6	Yes

United States**labor****U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals**

• Hydrogen sulfide	7783-06-4	1500 lb TQ
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed

• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Hydrogen sulfide	7783-06-4	100 lb final RQ; 45.4 kg final RQ
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	5000 lb final RQ; 2270 kg final RQ
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Hydrogen sulfide	7783-06-4	100 lb EPCRA RQ
--------------------	-----------	-----------------

• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Hydrogen sulfide	7783-06-4	500 lb TPQ
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Hydrogen sulfide	7783-06-4	1.0 % de minimis concentration
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	1.0 % de minimis concentration
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed

• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

• Hydrogen sulfide	7783-06-4	Not Listed
• Pentane	109-66-0	Not Listed
• Ethane	74-84-0	Not Listed
• 2-Methylbutane (In Liquid form)	78-78-4	Not Listed
• Isobutane	75-28-5	Not Listed
• Carbon dioxide	124-38-9	Not Listed
• Propane	74-98-6	Not Listed
• Butane	106-97-8	Not Listed
• Hexane	110-54-3	Not Listed
• Nitrogen	7727-37-9	Not Listed
• Methane	74-82-8	Not Listed
• 2-Propanethiol, 2-methyl-	75-66-1	Not Listed
• Methyl ethyl sulfide	624-89-5	Not Listed

Section 16 - Other Information

Last Revision Date

- 17/June/2014

Preparation Date

- 26/February/2006

Disclaimer/Statement of Liability

- The data contained in this SDS are believed to be accurate, but are not so warranted whether or not they originated at NW Natural. Recipients of this SDS are advised to confirm ahead of time that the data are current and suitable to their needs.

Key to abbreviations

NDA = No Data Available

Chemsico
 Division of United Industries Corp.
 P. O. Box 142642
 St. Louis, MO 63114-0642

Hazardous Material Identification System - (HMIS)

HEALTH - 1	REACTIVITY - 0
FLAMMABILITY - 2	PERSONAL -

Material Safety Data Sheet

Complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

I Trade Name: No-Pest® Wasp & Hornet Killer ₄			
Product Type: Aerosol insecticide			
Product Item Number: HG-41285 A		Formula Code Number: 21-1165/21-0666	
EPA Registration Number	Manufacturer		Emergency Telephone Numbers
9688-233	Chemsico Division of United Industries Corporation 8494 Chapin Industrial Drive St. Louis, MO 63114		For Chemical Emergency: 1-800-633-2873 For Information: 1-800-974-1271 Prepared by: Charlie Duckworth Date Prepared: November 3, 2011
II Hazards Ingredient/Identity Information		III Physical and Chemical Characteristics	
Chemical	%	OSHA PEL	ACGIH TLV
Light Petroleum distillate CAS#64742-47-8	4.00	100 ppm	100 ppm
Propylene glycol monobutyl ether CAS# 5131-66-8	2.00	None	None
Lambda-cyhalothrin CAS# 91465-08-6	0.01	NA	NE
d-trans allethrin CAS# 28434-00-6	0.05	NE	NE
Hydrocarbon Propellant blend CAS #75-28-5/106-97-8/ 74-98-6	3.50	NE	NE
IV Fire and Explosive Hazards Data		V Reactivity Data	
Flash Point: 119° F (TCC) (liquid portion)	Flame Extension: 0-inches (Level 1 Aerosol)	Stability: Stable	Polymerization: Will not occur
Flammable Limits: NA	Autoignition Temperature: NA	Conditions to Avoid: Temperatures over 130° F	Incompatible Materials: NA
Fire Extinguishing Media: Water fog, Carbon dioxide, Dry chemical	Decomposition Temperature: NA	Hazardous Decomposition or Byproducts: Carbon dioxide, carbon monoxide	
Special Fire-Fighting Procedures: Keep cans cool. Use equipment or shielding to protect personnel against bursting, rupturing or venting cans.	Unusual Fire & Explosion Hazards: At elevated temperatures (over 54° C/130° F), cans may vent, rupture or burst. Also see Section V.		
VI Health Hazard Data		VII Precautions for Safe Handling and Use	
Eye Contact: Causes moderate eye irritation. First Aid: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present after the first 5 minutes then continue rinsing eye. Call a Poison Control Center or doctor for treatment advice.	Special Notes: Have the product container with you when calling a Poison Control Center or doctor, or going for treatment.	Steps to be Taken in Case Material is Released or Spilled: Avoid breathing vapors. Avoid contact with liquid. Remove ignition sources. Soak up spills with absorbent material.	
Health conditions Aggravated by Exposure: None known	Ingredients listed by NTP, OSHA, or IARC as Carcinogens or Potential Carcinogens: None	Waste Disposal: Do not puncture or incinerate containers. If empty: Place in trash or offer for recycling if available. If partly filled: Call local solid waste agency for disposal instructions.	
VIII Control Measures		IX Transportation Data	
Read and follow label directions. They are your best guide to using this product effectively, and give necessary safety precautions to protect your health.		DOT: Consumer Commodity, ORM-D, UN-1950 IMDG: UN-1950, Aerosols, 2.1 IATA: UN-1950, Aerosols, Flammable, 2.1	

The information and statements herein are believed to be reliable but are not to be construed as warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.