

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**Product identifier**Trade name : Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID**Recommended use of the chemical and restrictions on use**

Use of the Substance/Mixture : Gear & lubricating oil.

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America EHS Customer Requests@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
--	---

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT	64742-55-8	Asp. Tox. 1; H304	89.99

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

 Valvoline™ ATF DEXRON III/MERCON
 AUTOMATIC TRANSMISSION FLUID

VE14838

PARAFFINIC DISTILLATE			
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC	64742-53-6	Asp. Tox. 1; H304	2.88
1-(tert-Dodecylthio)propan-2-ol	67124-09-8	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0.49

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Dizziness

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.

Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC	64742-53-6	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : red
- Odour : oily
- Odour Threshold : No data available
- pH : Not applicable
- Pour point : -44 °F / -42 °C
- : No data available
- Boiling point/boiling range : > 662 °F / 350 °C
- Flash point : 347 °F / 175 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0.859 g/cm³ (15 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Thermal decomposition :
No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 35 mm²/s (40 °C)

ca. 7.2 mm²/s (100 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous
reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition
products : carbon dioxide and carbon monoxide
Hydrocarbons

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:

Acute oral toxicity : LD 50 (Rat): > 5 g/kg

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

1-(tert-Dodecylthio)propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:

Result: Not irritating to skin

1-(tert-Dodecylthio)propan-2-ol:

Species: Rabbit

Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Slightly irritating to eyes

Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

Components:

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to eyes

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:

Result: Mildly irritating to eyes

1-(tert-Dodecylthio)propan-2-ol:

Species: Rabbit

Result: Not irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

1-(tert-Dodecylthio)propan-2-ol:

Assessment: May cause sensitization by skin contact.

Result: May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks: No data available

Carcinogenicity:**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

1-(tert-Dodecylthio)propan-2-ol:

Toxicity to fish : LC 50 (Oncorhynchus mykiss (rainbow trout)): 0.75 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other : EC 50 (Daphnia magna (Water flea)): 0.5 mg/l
aquatic invertebrates
(Chronic toxicity) Exposure time: 21 d
End point: see user defined free text
Test Type: see user defined free text
Method: OECD Test Guideline 211
GLP: yes

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological : An environmental hazard cannot be excluded in the event of
information unprofessional handling or disposal., Harmful to aquatic life
with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

General advice : The product should not be allowed to enter drains, water
courses or the soil.

Dispose of in accordance with all applicable local, state and
federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste
handling site for recycling or disposal.

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

 Valvoline™ ATF DEXRON III/MERCON
 AUTOMATIC TRANSMISSION FLUID

VE14838

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : No SARA Hazards

SARA 313 Component(s) : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	90.00 - 100.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	70.00 - 90.00 %
LUBRICANT ADDITIVE	Not Assigned	1.00 - 5.00 %
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC	64742-53-6	1.00 - 5.00 %

New Jersey Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	90.00 - 100.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	70.00 - 90.00 %
LUBRICANT ADDITIVE	Not Assigned	1.00 - 5.00 %
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC	64742-53-6	1.00 - 5.00 %

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

ASHLAND		Page: 12
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 12/9/2015
		SDS Number: 000000098044
Valvoline™ ATF DEXRON III/MERCON AUTOMATIC TRANSMISSION FLUID		Version: 1.0
VE14838		

KECL : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 06/01/2015

<p>NFPA:</p> <p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<p>HMIS III:</p> <table border="1"> <tr> <td style="background-color: #003366; color: white;">HEALTH</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #cc0000; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #ffff00; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	1	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Further information

Sources of key data used to compile the Safety Data Sheet
 Ashland internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 12/9/2015

SDS Number: 000000098044

Version: 1.0

Valvoline™ ATF DEXRON III/MERCON
AUTOMATIC TRANSMISSION FLUID

VE14838

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System